



Computer Hardware Design




CHD 87x0

All-in-one POS terminal

- ✓ 15" or 18.5" LCD display
- ✓ Competitive cost model
- ✓ High-performance models with Intel® CPU Braswell Celeron N3160
- ✓ Slim housing & compact footprint design
- ✓ Stylish modern design
- ✓ Fanless
- ✓ Robust Aluminum Alloy (die-casting) housing and stand
- ✓ Easy maintenance-Quickly disassembly of POS terminal and stand
- ✓ Various POS peripherals for all requirements
- ✓ IP65 protection for front panel housing

CHD 87x0 series hardware destined to be either POS Terminal or Panel PC, casts modern existence for its 15" or 18.5" true flat touch panel and streamlining shape. No matter which role it plays, CHD 87x0 series was born with a fanless system without boring noise that makes it perfectly fit to a variety of locations. In case it is placed in harsh environment, CHD 87x0 series incorporates die casting technology to its stand so as to give carefree utilization.





CHD 87x0

All-in-one POS Terminal



Computer Hardware Design

Specification	CHD 8750	CHD 8760	CHD 8770	CHD 8780
Motherboard				
Processor	Intel® Celeron® Processor N3060	Intel® Celeron® Processor N3160	Intel® Core™ Processor i5-6500TE	Intel® Celeron® Processor N3160
System Memory	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)	4GB, 1 x DDR4 (exp. up to 16GB) - 2133MHz (1.2V)	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)
LCD Touch Panel				
LCD Size	15" LED LCD	18.5" LED LCD	18.5" LED LCD	15" LED LCD
Brightness	300 cd/m²			
Resolution	1024 x 768	1366 x 768	1920 x 1080	1024 x 768
Touch Screen	True Flat Resistive	Projected Capacitive with 10 touch points		
Tilt Adjustment	TBS			
Storage Device				
Hard Drive	64 GB SSD, expandable	64 GB SSD, expandable	256 GB SSD, expandable	64 GB SSD, expandable
Expansion				
Mini PCI-E Socket	1			
External I/O Ports				
USB Port	4 x USB (2 x USB 3.0, 2 x USB 2.0)	6 x USB (2 x USB 3.0, 4 x USB 2.0)	6 x USB (2 x USB 3.0, 4 x USB 2.0)	4 x USB (2 x USB 3.0, 2 x USB 2.0)
Serial Port	4 x COM ports RJ-45 connectors (2 ports with power: 5V=green LED/12V=yellow LED, enabled by BOIS)			
Parallel Port	N/A			
LAN Port	1 x RJ-45 (10/100/1000Mbps Giga LAN)			
Second Display	1x HDMI (12V power by DC-jack, enabled in BIOS)			
Cash Drawer Port	1 x RJ-11 (12V/24V)			
DC Jack	1			
Audio Jack	1 x combo: mic & line out			
Audio				
Internal Speaker	1 x 2W	2 x 2W		1 x 2W
Power				
Power Supply	Adapter (DC 65W,19V,3.42A)	Adapter (DC 90W,19V,4.74A)	Adapter (DC 120W,19V,6.32A)	Adapter (DC 65W,19V,3.42A)
Control / Indicator				
Power Button	1			
Peripheral				
MSR	3 Tracks MSR USB (option)			
Finger print	1 (USB) (option)			
iButton	Option			
Second Display	2x20 VFD or 10.1 , 14" or 15" Second LCD Display with or without touch (option)			
Certificate				
EMC & Safety	FCC, CE			
Environment				
Operating Temperature	0°C to +60°C (+32°F to +140°F)			
Storage Temperature	-20°C to +80°C (-4°F to +176°F)			
Operating Humidity	10% to 90% RH non-condensing			
Storage Humidity	10% to 90% RH non-condensing			
Dimension (W x D x H)	360 x 200 x 340 mm	470 x 200 x 350 mm	470 x 200 x 350 mm	360 x 200 x 340 mm
Weight	5.6 kg	6.9 kg	6.9 kg	5.6 kg
Mounting	70mm x 70mm & 100mm x 100mm VESA mounting hole for panel PC type			
OS Installed	Windows® 10 Enterprise 2016 LTSC			
OS Supported	Linux, Windows® 8, Windows® 8.1, Windows® 10			