

Zebra XSLATE D10 Rugged Android Tablet

Product Specifications

DURABILITY	
Drop Test	MIL-STD-810G - 5' drop tested onto plywood over concrete
Hazardous Environment	C1D2 (Class 1 Division 2) and ATEX
Ingress	IP65
Internal	Magnesium-alloy internal frame
External	Durable corner bumpers
SYSTEM FEATURES	S
Operating System	Android™ 6.0.1, Marshmallow Android™ 5.1, Lollipop
Processor	• Intel® Atom™ E3845 Quad Core 1.91 GHz Processor)
Memory	• 4 GB DDR3L 1333 MHz
Storage Options	Standard 64 GB SSD Expandable via Micro SDXC Slot
Display	10.1" WXGA (1366 x 768) Rugged IPS LED Backlit Display 500 NITS Direct Bonded Screen 178° Viewing Cone (89° Off-Axis) Chemically Strengthened Glass Contrast Ratio: 800:1; Aspect Ratio: 16:9 Ambient Light Sensor (ALS) 10-Finger Multi-Touch, Glove Touch
Graphics	• Intel® HD Graphics (Gen 7)
Camera	Integrated rear 5 megapixel camera with flash Integrated Front 2 megapixel 1080P HD Webcam
Integrated Communications	Wireless LAN: 802.11ac Broadband: 4G LTE (Optional) GPS: Dedicated, Standard, 2.5m Accuracy Bluetooth® 4.0 LAN: 10/100/1000 Gigabit Ethernet (RJ-45)
Ports	DC Power 2 x USB 3.0 Ports Micro SDXC Micro HDMI-out Micro SIM Card Reader Headphones/Speaker Mini-Jack Stereo, Smart Phone Headphone Compatible
Integrated Options	• 1D/2D Barcode Scanner • HDMI-input
Battery Life & Power	Up to 8 Hour Battery Life (39.2 Whr, Single Battery) Hot Swappable External 2nd Battery Up to 15 Hour Battery Life (31.1 Whr, Dual Battery) Up to 22 Hour Battery Life (59.2 Whr, Dual Battery) Input Voltage: 19V with AC Adapter Supports 12∼20V Input DC on Tablet



Dimensions / Weight	• 11.05" (28.1 cm) x 7.07" (18.0 cm) x 0.86" (2.2 cm) (W x H x D) • Starting at 2.4 lbs (1.09 kg)
Security	Kensington® Cable Lock Slot Integrated Trusted Platform Module - TPM 1.2
Audio	Headphones/Speaker Mini-Jack Stereo, Smart Phone Headphone Compatible
Status Indicators	Power/Battery Status, Camera Active
SOFTWARE	
Software	XCapture Pro Panel Control Center Bios Setup Utility Touch Mode Switcher (Wet and Glove touch modes) Sierra Wireless Skylight Validity Finger Print Manager App Ublox u-Center Wacom Pen App Screen rotate PC info
WARRANTY	
Warranty	3 year standard coverage included

TESTING AND STANDARDS

Standards	Tested to: MIL-STD-461F
	 Immunity: CISPR 24, EN55024 (US, CAN, EU)
	 Emissions: EN55022, CISPR 22, CFR47 Part 15,
	Subpart B, ICES-003 for Class B (US, CAN, EU)
	• MIL-STD 464C: HERO, Safe Separation Distance = 0 ft
	 Safety: CB Scheme, IEC 60950 (US, CAN, EU),
	UL60079-0: 2013, UL60079-11: 2013 R3.14, CAN/
	CSA-C22.2 No. 60079-0: 11, CAN/CSA-C22.2 No.
	60079-11: 14, UL Class I Zone 2, A, B, C, D (US,
	CAN), ATEX Zone 2

IEC Ingress Testing	• IEC (60529) Ingress Tested to IP65 Standard

XSLATE D10 Android Tablet Specifications (continued)

Rugged & Environmental

- Tested to MIL-STD-810G Standards
- Operating Temperature: -34 °C to 60 °C / -30 °F to 140°F
- Cold Start: -20 °C / -4 °F
- Storage Temperature: -30 °C to 70 °C / -22 °F to 158 °F
- Transit Drop Operating: 5' (1.52 M) Drop Direct to Plywood over Concrete while System is Operating, 26 Drops
- Vibration: Minimum Integrity Non-operating, US Highway Truck and Composite Wheel Operating
- Shock: 40G Operating
- Humidity: 23 °C to 60 °C / 73 °F to 140 °F, 95% Non Condensing, 10 Days
- Natural Cycle Humidity: Fig 507.5-6, Non Hazardous B3 Class, 30 Days
- Water Proofness: Fig 506.5, 140L/hr, per sq/m, 15 Minutes
- Wind Driven Rain: Fig 506.5, 40 MPH Wind, 30 Minutes Per Side
- Blowing Sand: 20M/S, rate 1.1g/m3 (+/-.3g) at High Temperature of 60 $^{\circ}\text{C}$
- Blowing Dust: Velocity 8.9M/s Dust Concentration 3.9 g/m3 at High Temperature of 60 °C
- Temperature Shock: -30 °C to 70 °C / -22 °F to 158 °F within 5 Minutes
- Explosive Atmosphere: Method 511.5, @60 °C, 20,000ft, 10,000ft, and 5,000ft
- Contamination by Fluids: 50/50 Solution of Water and Bleach, 50/50 Solution of Water and Hydrogen Peroxide, Diesel Fuel, Mineral Based Oil, Lysol Disinfectant, Denatured Alcohol, Isopropyl Alcohol
- **Altitude**: 40,000 Ft (12,192 M) Operating, 50,000 ft 15,240m) Non Operating

Environment

- ROHS, Recycling Program: https://www.xploretech.com/about-us/environment/
- Energy Star 6.1
- CEC, Regulatory Bulletin No. 110915.02B (BCS), ERP Directive

ACCESSORIES

Docking

- xDock G2 IP55 Water and Dust-Resistant Vehicle Dock (12V compatible)
- Industrial Dock
- 2-bay and 6-bay Battery Charging Stands

Other Accessories

- Handle/Shoulder Strap with Pen and Tether
- Rotating Handstrap
- Kickstand
- Companion Keyboard
- Armortech Screen Protector
- External Battery Brackets, External 2nd Batteries
- 12-16V Input, 19V Output DC-DC Converter (Cigarette Lighter Adapter)
- 12-32V Input, 19V Output DC-DC Converter (Heavy Duty Cigarette Lighter Adapter)
- 18 60V Input, 13.8 V Output DC DC Converter, Direct Wire

Zebra acquired Xplore Technologies and all its products in 2018.

