

Product data sheet

Specifications



APC Easy UPS BVX 2200VA, 230V, AVR, IEC Sockets

BVX2200LI

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Input voltage	230 V AC 1 phase
---------------	------------------

Output voltage	230 V AC 1 phase
----------------	------------------

Rated power in W	1200 W
------------------	--------

Rated power in VA	2200 VA
-------------------	---------

Plug standard	IEC 60320 C20
---------------	---------------

Nb of power socket outlets	6 IEC 320 C19
----------------------------	---------------

Cable length	1.22 m
--------------	--------

Number of cables	1
------------------	---

Battery type	Lead-acid battery
--------------	-------------------

Provided equipment	User manual
--------------------	-------------

General

Max runtime	240 min
-------------	---------

Number of power module free slots	0
-----------------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

UPS size	WS
----------	----

Physical

Colour	Black
--------	-------

Height	19 cm
--------	-------

Width	14 cm
-------	-------

Depth	39 cm
-------	-------

Net weight	12.2 kg
------------	---------

Mounting support	Floor
------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.54

Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Standards	CE EN/IEC 62040-1 EN/IEC 62040-2
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah

Battery life	2...3 year(s)
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Package 1 Weight	13.2 kg
Package 1 Height	29.7 cm
Package 1 width	23.5 cm
Package 1 Length	49.5 cm
SCC14	10731304404528

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
