




Z30 POS Stand

For I-Series 4 Slate for Android



Integrated I/O



Concealed Cable Routing



Built-in CFD

Product Overview

The Z30 delivers a beautifully robust point-of-sale stand complete with a built-in customer-facing touchscreen display, integrated connectivity hub and concealed cable routing. Designed to support Elo's Android I-Series 4 Slate, the Z30 POS stand includes a universal VESA mount making it easy to install the 15.6-inch Full HD touchscreens with your choice of Qualcomm or Rockchip processor options.

Start changing the way customers and employees interact by deploying a new generation of interactive point-of-sale technologies that provide seamless integration, effortless provisioning and simplified device management via EloView or your preferred management tools.

Offer customers a point of interaction with an optional built in interactive CFD

Integrated connectivity hub built into the stand with a compartment for seamless cable routing

Compatible with the I-Series 4 Slate 15.6-inch Full HD interactive display

Z30 POS Stand

| Specifications | |
|-------------------------|---|
| Color | Dark Grey Metallic |
| Compatibility | Main Display: I-Series 4 Slate Customer-Facing Displays (for use of non-CFD stand): 0702L - Elo P/N: E796382 1002L - Elo P/N: E155834 and E324341 1302L - Elo P/N: E683595 and E683787 1502L - Elo P/N: E125496 |
| I/O Ports | DC Input 4 x USB-A 3.0 (900mA) RJ45 Ethernet LAN (Gigabit) RJ12 (Serial/cash drawer)* 12/24V Powered USB 24V USB-C output - CFD (DisplayPort, Touch and Power Delivery up to 27W) *User will need to select mode |
| Display Head Connection | USB Type C |
| Power | AC input voltage: 100-240 VAC Input frequency: 50-60 Hz |
| Power Consumption | On - Without CFD: 3.5W; With CFD: 8.32W Off: <0.1W Sleep - Without CFD: 2.5W; With CFD: 8.32W |
| Real-Time Clock | Lithium coin cell battery |
| Dimensions (W x D x H) | 6.34" x 9.55" x 7.99" / 162 mm x 242.6 mm x 203 mm |
| Shipping Dimensions | 11.65" x 11.42" x 12.6" / 296 mm x 290 mm x 320 mm |
| Weight | 5.7 lbs / 2.6 kg |
| Shipping Weight | 10.8 lbs / 4.9 kg |
| Temperature | Operating: 32°F to 104°F (0°C to 40°C) Storage: -4°F to 122°F (-20°C to 50°C) |
| Humidity | Operating: 20%-80% Storage: 5%-95% |
| Mounting Options | VESA 75mm |
| MTBF | 50,000 hours |
| Warranty | 2 years standard |
| Extended Warranty | 3 year warranty coverage - Elo P/N: E375367 4 year warranty coverage - Elo P/N: E375573 5 year warranty coverage - Elo P/N: E375771 2 year warranty coverage + AUR - Elo P/N: E375970 3 year warranty coverage + AUR - Elo P/N: E376169 4 year warranty coverage + AUR - Elo P/N: E376362 5 year warranty coverage + AUR - Elo P/N: E376547 |
| Regulatory Approvals | FCC (US) Class B (With CFD Model is Class A only); IC (Canada); CE (Europe); VCCI (Japan); RCM (Australia) |
| What's in the Box | Z30 POS Stand, North America Power Cable, European Power Cable, Quick Install Guide, 150W Power Brick, 2 x Zip Ties, 1 x M3 x6mm screws, 4 x M4x6 mm screws, 1 x M4x8 mm screw, Base Plate - for mounting to a countertop |

Built-In Customer-Facing Display

| Specifications | |
|---------------------|---|
| Size Resolution | 10.1 inch 1280x800 @ 60 Hz |
| Active Display Area | 8.7" x 5.3" / 216.96 mm x 135.6 mm |
| Operating System | Horizontal: ±80° or 160° total / Vertical: ±80° or 160° total |
| Processor | LCD Panel: 400 nits; TouchPro PCAP: 344 nits |
| Number of Colors | 8-bit (16.7M) |
| Touch Technology | TouchPro® PCAP (Projected Capacitive) - up to 10 touches |
| Sealing | Touchscreen sealed to LCD |

Ordering Information

| Part Number | Customer-Facing Display |
|-------------|---------------------------|
| E483135 | Z30 POS Stand Without CFD |
| E482940 | Z30 POS Stand With CFD |

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2022 Elo Touch Solutions, Inc. All rights reserved. 22061AES00163

