

HT730

4" Rugged Handheld Terminal



20 m reading distance | 2X2 MU-MIMO WLAN | 6700mAh hot swap battery | IP67 protect & 2.4 m Drop

Ergonomic One-Hand Operation with Large Keypad

Featuring a 4-inch display and 400nits brightness, the HT730 provides users to check feedback of the scanned information and easy viewing in outdoor environment. It comes with a large-size 38-key keypad as well as dual scanning buttons for instinctive data entry and barcode capturing that enables the users to carry out inventory checks and maintain accuracy easily. Moreover, equipped with special silicon materials and backlight design, it provides the reliability to 2.5 million lifetime clicks for long term abrasion protection.

Superior Imaging Technology

Ideal for tasks that require heavy scanning, the HT730 is built-in a powerful megapixel 2D scanning engine with a wide variety of 30 degree scanning tilt down design. The deice supports full barcode symbologies including 1D, 2D, Dot Code and OCR as well as boosts your scanning performance at a speed of 60fps. It also delivers motion tolerance of up to 5m/s, the HT730 increases the operation-al effectiveness even while moving.

Boost Wireless Communication Performance

The HT730 supports 2x2 MU-MIMO antennas that boost the wireless performance. Built in 4G dual-SIM slots, it provides double signal coverage and real-time communications even in different countries. Furthermore, it has a 13MP camera that gives an easy way to proof of delivery or shipment issues.

No Downtime with True Hot-Swap Battery

Featuring how-swap technology, the HT730 allows batteries to be swapped without interrupting within 1 minute. With a long-lasting 6700 removable battery, the HT730 allows continuous use for 20-26 hours operation and it is easily replaced whiles running out of power seamlessly.

Ultra-Durable & Flexibility Accessories

Design for harsh environments, HT730 features ultra-durable design to withstand 1.8m / 2.4m (with bumper) drop to concrete and IP65 / IP67 environmental seal against water and dust. Moreover, the HT730 offers options including a rugged gun grip, a rugged UHF RFID long-range reader, and even a rugged extra-long-range barcode scan engine that enhances the ease of use and increases staff comfort for inventory tracking and taking solutions.

Features

- · Android 10 OS with GMS certified
- Superior 2D scanning performance: Support 30-degree scanning tilt down
 - Durable keypad: 38-key / 29-key with 2.5 million lifetime clicks and backlight design
 - Ergonomic one-handed operation
 - Support Bluetooth[®] 5.1
 - Support IEEE 802.11a/b/g/n/d/h/i/k/r/v/ac/ax ready (8ss and TWT), 802.11ac Wave 2 with 2X2 MU-MIMO WLAN Standard
- 6700mAh battery for 20-26 hours operation
- True Hot-swap battery design without downtime
- 1.8 m drop-resistant housing (2.4 m with bumper)
- IP65/IP67 protection against water and dust
- Support MDM Software Solutions and utilities such as MoboLink, StageGO, and Ivanti Wavelink







unitech

Operation System

OS Android 10 GMS certified Octa-core 2.3 GHz, Qualcomm 720G (SM7125) CPU 4GB RAM / 64GB Flash Memory Languages support Multi-languages 5th Gen Qualcomm AI Engine AI

Display

Screen Size Touchpanel

Ultra-sensitive capacitive touch screen, compatible with gloves and support wet resistance

Keypad

Numeric (29 keys)/ Function Numeric (38 keys) with backlight

android

YES

Camera Rear 13 MP Autofocus with flash

Indicator LED, Speaker, Vibrator

4"TFT-LCD WVGA (480x800) color screen (400 nits)

Symbologies

UPC/EAN/JAN, GS1 DataBar, Code 39, Code 1D 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Matrix 2 of 5, MSI, Trioptic PDF417, MicroPDF417, GS1 Composite, 2D Code11, Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code, DOT Code Postal : Intelligent Mail Barcode, Postal-4i, Australian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code OCR : OCR-A, OCR-B, E13B (MICR)

Enclosure

Dimensions Weight

Power Source

Main battery Hot Swap Battery

Regulatory Approvals

CE, FCC, NCC, IC, VCCI, TELEC, CCC, SRRC, RoHS, CEC, BQB, GMS, N-Mark

Main battery 3.7V 6700mAh

Keeps applications active up to 1 minute

195 mm x 72 mm x 34 mm

395g(with battery)



Headquarters Taipei, Taiwan http://www.ute.com e-mail: info@hq.ute.com

unitech America Los Angeles http://us.ute.com e-mail: info@us.ute.com http://can.ute.com info@can.ute.com Mexico http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East Taipei

http://apac.ute.com info@apac.ute.com / info@india.ute.com http://mideast.ute.com info@mideast.ute.com

RFID

HF

Communication

Support HF/NFC Frequency 13.56Mhz

Bluetooth® 5.1

300Mbps/uplink 100Mbps

LTE (TDD) - Bands 38, 39, 40, 41

GPS, GLONASS, Galileo, BeiDou

USB 3.1 (type-C) support USB OTG

Custom IO connector (include USB Host)

Support Display Port Mode Ethernet/USB-Host via cradle

Yes, over USB Type-C

Nano SIM Slot x 2

cancellation

IP65 / IP67

UMTS/HSPA+ (3G) - Bands 1, 2, 5, 8

Support: ISO14443A/B, ISO15693 standard

IEEE 802.11a/b/g/n/d/h/i/k/r/v/ac/ax ready (8ss and TWT), 802.11ac Wave 2 (Dual Antenna, 2X2 MU-MIMO support)

GSM/GPRS/EDGE Quad-Band (850/900/1800/1900 MHz)

Gyroscope, G-sensor, E-compass, Light & Proximity Sensor

Micro SD/TF x 1(Support SD, SDHC and SDXC) up to 256GB

2W output ,105 dB at 10cm, Dual-Microphone, support noise

LTE Advanced Support Up to CAT4 LTE downlink

LTE (FDD) - Bands 1, 2, 3, 4, 5, 7, 8, 17, 20, 28

Bluetooth® WLAN WWAN

GPS Sensors

I/O Interfaces USB

> OTG POGO PIN SIM Slot Expansion Slot Audio

Durability **Drop Specification** Sealing

Environmental

Operating Temperature Storage Temperature Charging Temperature Relative Humidity

-20°C to +50°C - 30°C to 70°C (without battery) 0°C to 45°C 5% ~ 95% (non-condensing)

1.8 m / 2.4 m(with Bumper)

Software

SOTI, Ivanti Wavelink, AirWatch, 42Gears, and MoboLink

Accessories

USB Type C cable Single Slot Charging cradle Single Slot Ethernet cradle with USB host 4-Slot Charging cradle 4-Slot Ethernet cradle

4-Slot battery charger Hand strap **Glass Screen Protector**

unitech Europe Tilburg / Netherlands http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan Tokyo http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com



Specifications subject to change without notice. Copyright 2023 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

HT730 Specifications



Development Tools



Device Management

SOTI° SOTI° J2GEARS MWare° ivanti Wavelink

Staging and Management

HT730 Software Solution





MoboLink Android Enterprise ready EMM for monitoring device health and managing apps, configs

and files.



Monitor advanced Battery health and manage the battery replacement cycle. Use with MoboLink to get real-time attery health alerts delivered to your phone.



StageGO Barcode-based device staging utility offering hundreds of script commands for you to work with.



Software Update Check and install software updates online. To let a device always stay up-to-date, setup the device to automatically check and install for updates on boot up.



OEMConfig

If you are using a third party EMM, OEMConfig will allow those EMM solutions to configure unitech specific settings on the device.



System Update Center Check and install firmware

updates via FOTA. You can update the firmware via online FOTA server, or by using a OTA ZIP file placed in the internal storage.



Enterprise Launcher

Secure your devices by kiosking them with Enterprise Launcher. Block access to the Android system and only allow limited number of apps to be run.



App Update Center APKs install with App Update Center can remain intact even after factory reset.

0

File Manager Manage files and folders on all the internal and external storage options



Ivanti Velocity Android Terminal Emulator from Ivanti giving your workers the right tools to be more productive.

Productivity and Utilities



UNote A simple text viewer and editor for use in your work flows.



NTP Server Settings Customize the NTP server setting to keep your device date and time synchronized.



Startup Auto-run apps when device boots up.



WLAN Advanced Configure advanced WiFi parameters.



KeyRemap Reprogram physical buttons to act as another key or to launch an app.