

DECLARATION OF CONFORMITY

Manufacturers' Name: Honeywell International Inc Honeywell Scanning and Mobility Fort Mill, SC 29707 USA	European Representative: Honeywell International Inc Honeywell Scanning and Mobility Nijverheidsweg 9-13 Eindhoven, 5627 BT The Netherlands Phone: +31 40 290 16 00
---	---

Honeywell declares under its sole responsibility that the Honeywell products described below conform to Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment, as amended.

Referenced harmonized standards and/or technical specifications:

EN 50581:2012 "Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances"

Additional information:

None

Honeywell Products:

162829-0001	CBL, MPP USB ADPTR
162830-0001	CBL, MPP RS232 ADPTR
162831-0001	CBL, MPP RS232+USB
42203758-01E	Cable: RS232 TTL, Power on Pin 9, TX Data on Pin 2 Connector: D 9 PIN M Length: 7.7 ft. (2.4m), coiled
42203758-02E	Cable: RS232 TTL 'EP' Connector: 9 Pin D 9 PIN F, 4 Pin Mini Din Length: 7.7 ft. (2.4m), coiled
42203758-03E	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, coiled Length: 7.7ft. (2.3m)
42203758-03SE	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, straight Length: 7.7ft. (2.3m)
42203758-04E	Cable: RS232 TTL, Connector: D 9 Pin F connector, TX data on pin 2, external power, coiled Length: 7.7ft. (2.3m)
42203758-06E	Cable: RS232 TTL, 9 F 'EP' 15', D 9 PIN F, Mini Din 4 PIN Length: 7.7 ft. (2.3m), coiled
42203764-03E	Cable: Wand Emulation, Power on Pin 9 Connector: D 9 PIN Squeeze Length: 7.7 ft. (2.3m), coiled
42203764-04E	Cable: Wand Emulation, power on Pin 4 Connector: D 9 PIN Squeeze Length: 6.8 ft. (2.0m), coiled
42204064-01E	Cable: IBM 3151.3471.3472, Connector: Modular 8 PIN M/F Length: 8.5 ft. (2.6m), coiled
42204253-01E	Cable: RS232, Power on Pin 9, TX Data on Pin 2 Length: 7.7 ft. (2.4m), coiled
42204253-03E	Cable: RS232, power on Pin 9, TX Data on Pin 2 Connector: D 9 PIN F Length: 7.7 ft. (2.4m), coiled
42204253-04E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN F and Mini Din 4 PIN F, 2.3m (7.7'), coiled, external power
42204253-05E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN F and Mini Din 4 PIN F, 5.0m (16.3'), coiled, external power

DECLARATION OF CONFORMITY

42204253-22E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN M/F and Mini Din 4 PIN F, 6.8m (22.3'), coiled, external power
42204841-01E	Cable: direct connect, Connector: Mini Din 6 PIN M Length: 7.7 ft. (2.3m), coiled
42204254-01E	CBL, 55/30, RS232, 25PIN MALE
42204906-01E	Cable: 55/30 extender Cable: Connector: Modular 8 PIN M/F, coiled
42204933-01E	Cable: Wand Emulation, Connector: Din 5 PIN M (w/ lock) Length: 6.8 ft. (2.1m), coiled
42205021-01E	Cable: AT - PS/2 & Compatibles, EP, wedge (3.0ft. .91m), straight
42205155-02E	Cable: IBM 46xx, black, RS485 Port 9A/B, 3.7m (12.2'), coiled, Connector: SDL 4 PIN A Key
42205155-04E	Cable: IBM 46xx, black, RS485 Port 9A/B, 7.0m (23.0'), coiled
42205155-05E	Cable: IBM 46xx, black, RS485 Port 9A/B, 3.1m (10.2'), coiled
42205626-03E	Cable: RS232, black, DB9, 2.3m (7.7'), external power, coiled
42205895-01E	Cable: RS232 TTL, black, coiled, 2.3m (7.7'), power from PS-2 keyboard/mouse port
42205910-04E	Cable, RS-232, EP Connector: 9 PIN D F Length: 4.2 ft. (1.3m), straight
42205978-01E	Cable: HHLC/laser emulation Connector: D 9 PIN Squeeze Length: 6.8 ft. (2.0m), coiled
42206090-01E	Cable: RS232 TTL out Mod 8 Pin M Length: 7.7 ft. (2.4m), straight
42206092-01CE	Cable: AT - PS/2 & compatibles ESD/cleaned, wedge Connector: Mini Din 6 PIN M/F Length: 7.0 ft. (2.1m)
42206132-01E	Cable: AT - PS/2 & compatibles wedge, EP, Connector: Mini Din 6 PIN F Length: 15.5 ft. (4.7m), straight
42206132-02E	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), coiled
42206132-02SE	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), straight
42206132-03E	Cable: AT - PS/2 & compatibles wedge, EP Connector: Mini Din 4 PIN F Length: 9.2 ft. (2.8m), straight
42205895-01E	Cable: HSM RS232 TTL, 3400
42206161-01E	Cable: USB, black, Type A, 2.6m (8.5'), straight, host power
42206162-01E	Cable: USB, black, 12V locking, 2.6m (8.5'), straight, host power
42206200-01E	Cable: coiled direct connect 3800-II connector Connector: Din 7 PIN M (with lock) Length: 15.7 ft. (4.8m)
42206202-01E	Cable: USB, black, secondary interface Length: 9.2 ft. (2.8m), coiled
42206202-02E	Cable: USB, black, Type A, 2.8m (9.2'), coiled, host powered
42206212-02E	Cable: Combo kit with resistor Connector: Mini Din or Din PCs and PS/2 Length: 9.2 ft. (2.8m)
42206236-01E	Cable: 3800 Direct Connect Length: 7.7 ft. (2.4m), coiled
42206287-01E	Cable: RS232 TTL, power on Pin 9 + 12 VDC Connector: D 9 PIN F Length: 7.7 ft. (2.3m), coiled
42206300-01E	Cable, RS-232 TTL output, Connector: D 9 PIN M Length: 7.7 ft. (2.4m), coiled
42206301-01E	Cable: RS232 serial out, coiled
42206338-01E	Dolphin Series straight USB charging and communications cable (not compatible with 3800g)
42206339-01E	Dolphin Series RS-232 charging and communications cable
42206415-01E	CABLE, KEYBOARD EMULATION CUSTOM
42206416-01E	Cable: USB, black, Type A, coiled, 2.6m (8.5'), external power
42206422-01E	Cable: RS232 TTL, black, DB9, 2.3m (7.7'), straight, 5v external power
42206431-01E	Cable: USB, black, Type A, 3.4m (11.1') coiled, host power (Use w/3800VHD-ESD-12E. Not compatible with 3800g)

DECLARATION OF CONFORMITY

42206433-DIE	Cable: USB,+5V, 8.5FT, straight cable ending in right angle (8.5ft, 3.7m)
425388-0406	CABLE, USB A MALE TO USB
427508-0630	CBL ASSY, MINI DNG M/F
427518-0913	CBL ASSY, D9 M/F 1:1 ST
50101284-001	Cable,VSD,3310G
50118069-001	USB Multi Checkpoint
50118071-001	RS232 Multi Checkpoint
52-52511	Cable: Checkpoint EAS, 0.6m (2.0'), straight
52-52556	Cable: Checkpoint EAS, 1.8m (6.0'), straight
52-52557-3-FR	Cable: RS232, black, DB9, 5V, 2.9m (9.5') straight
52-52558-3-FR	Cable: KBW, black, 3.0m (9.8'), coiled, 5V external power with ferrite
52-52559-3-FR	Cable: USB, black, Type A, straight, 5V external power with ferrite
52-52559-N-3-FR	Cable: USB, black, Type A, 5V, 2.9m (9.5') straight
52-52561-3-FR	Cable: USB, black, Type A, 5V, 2.9m (9.5') straight, External ID
52-52562-3-FR	Cable: RS232, black, DB9, 5V, 2.9m (9.5') straight, External ID
52-52861A	CABLE: USB OPTIMUS CRADLE
52-52828-3	Cable: USB, black, Type A to Type B
53-53000-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, 5V external power
53-53000-N-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, host power
53-53002-3	Cable: KBW, black, 2.9m (9.5'), coiled, 5V external power
53-53002-N-3	Cable: KBW, black, 2.9m (9.5'), coiled, host power
53-53004-I2	Cable: RS232 Aux, gray, RJ45, 3.8m (12.5'), coiled, 5V external power
53-53004-N-3	Cable: RS232 Aux, black, RJ45, 2.9m (9.5'), coiled, host power
53-53014-3	Cable: RS232, black, 2.9m (9.5'), coiled, 5V external power
53-53020-3	Cable: Single keyboard cable, black, 2.9m (9.5'), coiled, 5V external power
53-53020-N	Cable: Single keyboard cable, black, 2.9m (9.5'), coiled, host power
53-53068-N-3	Cable: USB, black, 5V Locking, 3.9m (12.8'), coiled, host power
53-53089-3	Cable: RS232, black, 2.9m (9.5'), coiled, 5V external power
53-53124-3	Cable: RS232, black, DB9 female, 3.7m (12.1'), coiled, 5V external power
53-53125-3	Cable: RS232, black, DB9 female, 6.1m (20.0'), coiled, 5V external power
53-53153-N-3	Cable: RS232 Wincor, black, DB9 male, 2.9m (9.5'), coiled, host power
53-53213-N-3	Cable: USB, black, 12V locking, 2.9m (9.5'), coiled, host power
53-53213-N-3-FR	Cable: USB, black, 12V locking, 2.9m (9.5'), coiled, host power with ferrite
53-53235-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, 5V external power
53-53235-N-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power
53-53235-N-3-FR	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power with ferrite
53-53235G-N-3	CABLE,USB LS,COIL,DIRECT Ruby Grey
53-53283-N-3	Cable: USB, black, Type A, 3.8m (12.5'), coiled, host power
53-53283-N-3-I5	Cable: USB, black, Type A, 4.6m (15.1'), coiled, host power

DECLARATION OF CONFORMITY

53-53290-N-3	Cable: RS232, black, DB9 male, 3.9m (12.8'), coiled, host power
53-53802-N-3	Cable: KBW, black, 2.9m (9.5'), coiled, host power
53-53809-N-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power
53-53809-N-3-16	Cable: USB, black, Type A, 4.9m (16.0'), coiled, host power
54-54073-3	Cable: Y type BT FS USB plug connector, straight
54-54165-3	Cable: USB, black, Type A, straight, 5V external power
54-54667-14	Cable: RS232 LSD, gray, 4.3m (14'), straight, 5V external power
55-55000-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, 5V external power
55-55002-3	Cable: KBW, black, 2.4m (7.9'), straight, 5V external power
55-55146-3	CABLE,RS232SRT, LONGSRSPEC DB9
55-55165-3	Cable: USB, black, Type A, 1.5m (4.9'), straight, 5V external power
55-55235-N-3	Cable: USB, black, Type A, 2.9m (9.5'), straight, host power
55-55235C-N-3	CABLE,5145 USB Straight, Type A 2.9M black
55-55535-N-3	Cable: KBW, black, Type A, 1.9m (5.7'), straight, host power
55-55809-N-E-3	Cable: USB, black, Type A and 2 wire pigtail, straight, host power with EAS
57-57000-N-3	Cable: RS232, black, DB9 female, 3.6m (11.8'), straight, no power
57-57004-N-3	Cable: IBM 46xx, black, 4-pin SDL, straight, no power
57-57006-N-3	Cable: USB, black, Type A, 3.6m (11.8'), straight, no power
57-57008-N-3	Cable: StratosSchool, RS232 Aux, black, straight, host power
57-57099-3	Cable: RS232 Aux, black, 10-pin RJ45, 2.9m (9.5'), straight, host power (voyager/eclipse)
57-57099-3-12	Cable: RS232 Aux, black, 10-pin RJ45, 3.7m (12'), straight, host power (voyager/eclipse)
57-57200-N-3	Cable: USB, black, 12V locking, 2.7m (8.9'), straight, no power with ferrite
57-57201-N-3	Cable: USB, black, Type A, 4.0m (13.1'), straight, no power with ferrite
57-57210-N-3	Cable: RS232, black, DB9 female, 3.6m (11.8'), straight, no power
57-57227-N-3	Cable: USB, black, 12V locking, 4.0m (13.1'), straight, no power
58-58056-N-3	Cable: SING END,2 FT,KB
59-59000-3	Cable: RS232, black, DB9, 2.9m (9.5'), straight, 5V external power
59-59002-3	Cable: KBW, black, 2.4m (7.9'), straight, 5V external power
59-59002-N-3	Cable: KBW, black, 2.4m (7.9'), straight, host power
59-59014-FR	Cable: RS232 MetroSet cable, gray, straight, 5V external power with ferrite
59-59084-N-3	Cable: USB, black, Type A, 2.9m (9.5'), straight, host power
59-59194-N-3-14	Cable: RS232, black, 4.3m (14.1'), straight, host power
5S-5S213-N-3	Cable: USB, black, 12V locking, 2.9m (9.5'), straight, host power
60S-DB9CABLE	D60S DB9 cable
60S-DEXCABLE	D60S DEX cable
7600-RS232 E	Dolphin 7600 RS-232 charging and communications cable
7600-USB E	Dolphin 7600 USB charging and communications cable
80000355E	6 ft. (1.8m) USB Cable
830005ICABLE	8FT POWERSCAN CABLE, D9F

DECLARATION OF CONFORMITY

9000052CABLE	CABLE, COMBO, 1FT, USB MASTER, ETHRNT, D15 TO RJ45 AND USB-A
9000054CABLE	CABLE, 12 FT, INPUT POWER
9000063CABLE	CABLE, 6 FT, UPS BATTERY, REMOTE
9000072CABLE	CABLE, COMBO, 1FT, DUAL PS2 ADAPTR, D9 TO DUAL MIN-DIN
9000075CABLE	CABLE, COMBO, 1FT, VX6-VX7 D15 TO RJ45, USB-A, USB-A PLUG
9000076CABLE	MX3Plus Headset coiled adapter cable, includes quick disconnect headset connector to a 2.5 mm audio jack. A headset is still required.
9000077CABLE	CABLE, 1 FT, ADAPTR, POWER, VX1, VX2, VX4, VX6, VX7
9000A054CBL609D9	Cable, Serial Null Modem, PC, D9F to D9F, 6ft, ActiveSync
9500-RS232-IE	Dolphin Series RS-232 charging and communications cable, power supply, and cord (U.S. kit)
9500-USB-IE	Dolphin Series USB charging and communications cable, power supply, and cord (U.S. kit)
A023801	SAT401 EXTENSION CABLE - 5M
A023802	SAT401 EXTENSION CABLE - 10M
A023803	SAT401 EXTENSION CABLE - 15M
A023804	SAT401 EXTENSION CABLE - 20M
A023805	SAT401 EXTENSION CABLE - 25M
A023806	SAT401 EXTENSION CABLE - 30M
A023807	SAT401 EXTENSION CABLE - 0.3M
A06802	SAT401 EXTENSION CABLE - 5M (25way)
A062801	SAT401 POWER CABLE (Cigar to DC) -2M
A058801	SAT401 PA Button (Hand Held)
CBL-000-200-S00-01	CBL, VMS BDG RDR, Weigand, 2M
CBL-000-200-S00-03	CBL, VSU Canbus, 2M
CBL-000-200-S00-05	CBL, VSU Canbus with resistor, 2M, VSU
CBL-000-240-C00	CBL,RS232,TTL OUTPUT, 1400G
CBL-000-250-C00	CBL, HSM 5V 232 TTL, 2.5M
CBL-000-300-C00	Cable: RS232 TTL OUT
CBL-000-300-C00-01	RS232TTL OUT, INDUSTRIAL
CBL-000-300-S00	CBL, PS-2 KBW, HSM 5V
CBL-020-150-C00	1.5m RS232 host cable
CBL-020-150-S00-01	Cable, RS232 5V, 1.5M, YJ HF500
CBL-020-270-S00	2.7m RS232 host cable
CBL-020-270-S00-01	Cable, RS232 5V, 2.7M YJ HF500
CBL-020-290-S00	Cable, RS232, Black, DB9, 5V, 2.9M
CBL-020-290-S00-01	Cable, RS232, Black, DB9, 5V, 2.9M ID
CBL-020-300-C00	Cable: RS232 (5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-020-300-C00-01	Cable, RS232, 5V Signal, DB9F, Coiled, 3M, IND

DECLARATION OF CONFORMITY

CBL-020-500-C00-02	CBL,RS232TTL,5V,DB9PFEMALE LE,COIL,5M,UPS
CBL-120-300-C00	Cable: RS232C (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-150-650-S00	Drawing, CBL, RS232, 12V, 7820
CBL-200-200-S00	Cable, VSU to USB DB9, 2M, VMS
CBL-200-300-C00	Cable: HSM, 5V 232 TTL
CBL-210-300-C00	Cable
CBL-210-300-C00-01	Cable
CBL-220-300-C00	Cable: RS232 (+5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle
CBL-320-300-C00	Cable: RS232 (+/-12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9
CBL-400-061-S00	CABLE RS232, 10P10C PLUG
CBL-400-150-S00	Cable is E157914 PRIMAX RU AWM 20099 60C 150V VW-I CSA LL110529 AWM I/II A/B 60C 150V FTI
CBL-400-190-S00	HDB 15P FM to 10P10C Cable
CBL-400-250-C00	CBL, KEYBOARD EMULATION,1400G
CBL-400-250-S00-00	CBL,AUX 5V, 3310G to DATALOGIC, 2.5M
CBL-400-250-S00-02	CBL,AUX 5V, 3310G to NCR, 2.5M
CBL-400-300-C00	CBL, HSM 5V 232 TTL, AUX, 3M
CBL-400-300-S00	cable aux, 5V3310G to statos
CBL-420-300-C00	Cable: RS232 (5V signals), Honeywell Bioptic Stratos Aux, black, 10 pin modular, 3m (9.8'), coiled, host power possible (dependent upon scanner and Stratos models)
CBL-420-300-C00-01	E,RS232,5V BIOPTIC AUX,3M,INDUSTRIAL
CBL-431-300-S00	Cable: RS232 (+/-12V signals), Verifone Ruby, Sapphire and Topaz Terminals, black, 8 pin modular; straight, host power on pin 8
CBL-431-300-S00-01	USB TYPE A to Mini 10PIN PLUG, 2A
CBL-500-050-S00	CABLE, USB 5V, 0.5M, 3310G
CBL-500-070-S00	CABLE, USB 5V
CBL-500-100-S00-00	CABLE, MINI USB, ISLED V2
CBL-500-120-S00-00	CABLE, STANDARD MINI USB, ISLED V2
CBL-500-120-S00-03	Cable, Micro USB, 1A8, EDA50
CBL-500-120-S00-04	CBL, USB, Micro B to Type A
CBL-500-150-S00	USB Type A HSM 5V 1480mm straight
CBL-500-150-S00-03	CBL USB 1.5M Type A HSM 5V
CBL-500-200-S00-01	Cable: CBL USB 2M, Type A, HSM

DECLARATION OF CONFORMITY

CBL-500-200-S00-02	USB A type to Micro B, 2M
CBL-500-200-S00-04	Cable, VSU to USB Type A, 2M, VMS
CBL-500-270-S00-01	CBL,USB 5V, 2.7M YJ HF500
CBL-500-290-S00	Cable, USB, Black, Type A, 5V, 2.9M
CBL-500-300-C00	Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power
CBL-500-300-C00-03	Cable: USB Type A, Coiled, 3M
CBL-500-300-C00-04	Xenon RS232 cable
CBL-500-300-S00	Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power
CBL-500-300-S00-02	CBL,USB W/Ferrite, Type A, HSM 5V
CBL-500-300-S00-03	CBL,USB W/Ferrite, Type A,5V Industrial
CBL-500-300-S00-04	CBL, USB Type A, HSM 5V
CBL-500-500-C00	Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power
CBL-500-700-C00	CBL, USB Type A, Coiled, 7m
CBL-503-150-S00	CBL,USB RETAIL,12V KEY
CBL-503-300-C00	Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power
CBL-503-300-S00	Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power
CBL-503-500-C00	Cable: USB, black, 12V locking, 5m (16.4'), coiled, 5V host power
CBL-520-290-S00	Cable, USB, Black, Type A, 5V, 2.9M IO
CBL-530-370-S20-BP	USB, Powered, 12V Locking, 3.7m
CBL-600-300-S00-01	CBL, IBM 4683 Port 9D, HSM 5V
CBL-600-400-C00	Cable: IBM 46xx Port 9b, 12V Power, coiled, 4m (13.1')
CBL-700-300-S00	CBL, 232 TTL,HSM 5V
CBL-720-290-S00	Cable, KBW, Black, PS2, 5V, 2.9M
CBL-720-300-C00	Cable: KBW, black, PS2, 3m (9.8'), coiled, 5 V external power with option for host power
CBL-860-100-S02	CBL, EAS, Checkpoint, 7980G
CBL-860-200-S04	CBL, EAS, Sensormatic, 7980G
CBL-GIL-300-S00-02	Cable: RS232 (5V signals), Gilbarco terminal, black, DB9 Female, 3m (9.8'), straight
CBL-NCR-300-S00	Cable: RS232 (5V signals), NCR 787x, black, 8 pin modular, 3m (9.8'), straight, external power with option for 5V host power on pin 1
CBL-WNC-500-S20-BP	RS232 DB9 MALE 5M
MVC-2MPC-1B9	CABLE,IBM PORT 9,10 PINRJ45 MALE,COILE
MVC-3FPS-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 0.6m (2.1'), straight, host power
MVC-3MPC-1B9	Cable: IBM 46xx, black, Port 9 4-pin SDL, 3.1m (10.2'), coiled, 9V host power
MVC-3MPC-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 3.3m (10.7'), coiled, host power
MVC-3MPC-VR3750	Cable: Verifone-Ruby 3750 Terminal, black, 8-pin Mod, 3.5m (11.5'), coiled, host power
MVC-3MPS-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 2.3m (7.4'), straight, host power
MVC-3MPS-VR3750	Cable: Verifone-Ruby 3750 Terminal, black, 8-pin Mod, 2.3m (7.4'), straight, host power
MX-232C-153-3	Cable: RS232, black, DB9 male, 2.9m (9.5'), straight, host power with TTL to 12V converter
VPS052CABLE	Cable, VPS VSU to USB Type A, 2M

DECLARATION OF CONFORMITY

VPS053CABLE	Cable, VPS VSU to VMC D9 (Spare) /EXTN Cable
VPS054CABLE	Cable, VPS Badge Reader (Spare), 2M
VPS054CABLE	Cable, VSU I/O Connector, 2M

Signed for and on behalf of	Honeywell International Inc
Place and Date of Issue	9680 Old Bailes Road Fort Mill, SC 29707 USA 20-September-2016
Name and Title	Don Douthit, Global Manager, Regulatory Compliance Honeywell Scanning & Mobility
Signature	