



1717L 17-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1717L 17-inch standard aspect touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set makes it an attractive solution for commercial touchscreen monitor needs. The 1717L is well suited for point-of-sale, point-of-information, point-of-service, interactive signage and loyalty systems.

The 17-inch touchscreen offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Available touch technologies:

- AccuTouch® Resistive
- IntelliTouch® SAW

Customize with an integrated 3-track magnetic stripe reader (MSR)

Desktop, wall or VESA mounting

1717L 17-inch LCD Touchscreen Monitor

Specifications	
Model	1717L
Color	Black or white
Active Display Area	13.3" x 10.64" (337.92mm x 270.34mm)
Monitor Dimensions (with stand)	15.43" x 8.38" x 14.24" (391.9mm x 215.4mm x 361.6mm) (dimensions vary with stand position and options selected)
Monitor Thickness	1.7 inches (43mm) panel depth
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	17.0"
Aspect Ratio	5:4
Native (Optimal) Resolution	1280 x 1024
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768, @ 60Hz, 75Hz; 1280 x 1024 @ 60Hz, 75Hz
Number of Colors	16.7 million
Number of Touches	Single-touch
Brightness (typical)	LCD Panel: 250 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits; IntelliTouch ZB: 225 nits
Response Time - Total (typical)	5 msec
Viewing Angle (typical)	Horizontal: +/-85° or 170° total; Vertical: +/-80° or 160° total
Contrast Ratio (typical)	1000:1
Video	Analog VGA on Female DB-15 connector Input Video Horizontal Sync frequency range: 31.5-80KHz, Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor AC input power connector: IEC 60320 C6 Monitor AC input voltage specifications: 100-240VAC, 50/60Hz Monitor DC input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter) Monitor DC input voltage specifications: 12VDC +/- 5% Note: Optional AC-DC power adapter sold for this monitor: AC input connector: IEC 60320 C14 AC input voltage specification: 100-240VAC, 50/60Hz Power Consumption (Typical): ON (monitor): 11.5W; SLEEP (monitor): 1.2W; OFF (monitor): 0.4W
Replacement DC Power Supply	The monitor may be powered with DC voltage. A optional 12V DC power brick, Elo P/N: E005277, is available at additional cost.
AC Power Cable	North American & EU power cables included. UK AC power cables included with P/Ns available for EMEA. China: E501749, UK: E540272
Weight (with stand)	Unpackaged: 11.9 lbs (5.4 kg); Packaged: 18.3 lbs (8.3 kg)
Shipping Dimensions	20.12" x 9.17" x 20.08" (511mm x 233mm x 510mm)
Mounting Options	75 mm VESA mount, capped through-mount holes
On-Screen Display (OSD)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H- position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	Argentina S-mark, Australia RCM, Canada cUL, IC, China CCC, Europe CE, Japan VCCI, Korea KCC, e-Standby, Mexico NOM, Taiwan BSMI Mark, United States UL, FCC, International CB, RoHS, China RoHS, WEEE
Touch Interface	Serial (RS232) and USB
Warranty	3 years standard
Extended Warranty Options	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	QIG, VGA cable (DB-15 male to DB-15 male), USB cable (USB Type A plug to USB Type B plug), power cable, IEC 60320-C5 to NA/EU plug, stand base assembly, filler plate

Ordering Information

Part Number	Technology	Interface	Bezel	Surface Treatment	Color
E877820	AccuTouch	Serial/USB	Yes	Antiglare	Black
E649473	AccuTouch ZB	Serial/USB	No	Antiglare	Black
E077464	IntelliTouch	Serial/USB	Yes	Antiglare	Black
E179069	IntelliTouch ZB	Serial/USB	No	Clear	Black
E017030	IntelliTouch ZB	Serial/USB	No	Antiglare	Black

Learn more about Elo at EloTouch.com.

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
Elo.Asia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and IntelliTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2021 Elo Touch Solutions, Inc. All rights reserved. 21031AES00007

