

METAPACE

Metapace S-22 – Portable 2D barcode reader with a large range

www.metapace.com

Highlights

- Wireless area imager for all common 1D and 2D barcodes
- High flexibility thanks to Bluetooth (up to 90 m range)
- Changeable handheld and presentation usage
- For a double shift: battery life up to 16 hours
- Powerful, proven scanning engine for quick capture

Technical specifications

Scanner properties

Type	2D area imager
Light source	625 ±5 nm LEDs (2 x)
Resolution	1D barcode: 3 mil, 2D barcode: 5 mil
Scan rate	60 scans/second; 60 decodes/second
Depth of field	3.6 cm - 30.5 cm
Scanning angle	Pitch: ±60 °; skew: ±60 °
Hands-free scanning	Auto-sense and presentation mode
Supported barcodes	All standard 1D and 2D barcodes
Language support	English, French, Italian, Belgian, Norwegian, Swedish, Portuguese, German, Spanish, Japanese, Turkish

Electronics

Module	Bluetooth class 2 (2.4 GHz) Version 2.0 + EDR
Bluetooth range	Up to 90 m line of sight
Voltage	+5 V ± 10 % / 800 mAh Li-ion battery

Interfaces

I/F ports	USB, KBW, RS232
-----------	-----------------

Specifics

Impact resistance	1.2 m multiple drops onto concrete
Protection rating	IP30
Accessories	Three-position stand for presentation mode, tabletop and wall mounting; connection of up to seven scanners per cradle via Bluetooth
Configuration	Setup using Windows-based Metapace ScanMaster software (included), by direct connection or printed bar codes

Housing

Weight	185 g
Colour	Black

Environment

Operating temperature	0 up to 50 °C
Storage temperature	-20 up to 60 °C
Humidity	10 up to 90 % RH (non-condensing)

Warranty

Period	36 months (except battery)
--------	----------------------------

Area Bluetooth
Imager

