OPN 2001

Pocket Memory Scanner



Product Features

USB communication interface

For easy data transfer the device is equipped with a standard USB port, which is also used to charge the internal battery.

Large internal memory

Over 10.000 codes can be stored and removed by the user at any time

Lightweight (only 28 grams)

Provides mobility and flexibility

Two button operation

Plain and simple to use



Specifications OPN 2001 Pocket Memory Scanner

Electrical specifications

Main battery pack: Lithium-Ion rechargeable (3.7 V DC, 150 mAH)

Main battery pack operating time: 1000 scans (conditions: every scan 4 sec. laser beam on / 1 sec. good read LED on)

Charging method: Recharging lithium-Ion pack in scanner via USB port

Optical specifications

Light source: 650 nm visible laser diode

Scan method: vibrating mirror

Scan rate: 100 scans/sec

Decode rate: 100 decodes/sec

Reading pitch angle: -35 to 0°, 0 to +35° Reading skew angle: -50 to -8°, +8 to +50°

Reading tilt angle: -20 to 0°, 0 to +20° Curvature: R>15 mm (EAN8), R>20 mm (EAN13)

Min. PCS value: 0.45

Depth of field: at PCS 0.9, UPC

60 - 570 mm / 2.36 - 22.44 in (res. 1.0 mm / 39 mil),

40 - 360 mm / 1.57 - 14.17 in (res. 0.5 mm / 20 mil),

40 - 220 mm / 1.57 - 8.66 in (res. 0.25 mm / 10 mil),

40 - 120 mm / 1.57 - 4.72 in (res. 0.15 mm / 6 mil),

50 - 100 mm / 1.97 - 3.94 in (res. 0.127 mm / 5 mil)

Communication specifications

Available interfaces: USB

Identification

Supported barcode symbologies (1D): JAN/UPC/EAN (WPC) incl. add on, Chinese Post, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Korean Postal Authority code, Matrix 2of5, MSI/Plessey-UK/Plessey, RSS, S-Code, Telepen, Tri-Optic

Functionality

Memory FlashROM: 512 kB (Program storage + >1000 barcodes + time stamp)

Memory RAM: 64 kB

Microprocessor: ARM7, 32 bits

Real time clock: Quartz RTC, time and date programmable, leap year handling,

(accuracy +/- 60 sec./month)

Keyboard: 1 scan button, 1 clear button O/S: proprietary

Environmental specifications

Temperature in operation: -10 to 40 °C / 14 to 104 °F

Temperature in storage: -20 to 60 °C / -4 to 140 °F

Ambient fluorescent light rejection: 4,000 lx max.

Ambient white light rejection: 4,000 lx max. Ambient direct sun light rejection: 80,000 lx max

Physical specifications

Dimensions: 30 x 62 x 16 mm / 1.18 x 2.44 x 0.63 in

Weight body: Ca. 28 g / 1 oz


Regulatory

Laser safety class: JIS-C-6802 Class 1, IEC 60825-1 Class 1, FDA CDRH Class I

Product compliance: CE, FCC, VCCI, RoHS


Depth of field

Unit: mm (in)



Dimensions

unit: mm (in)



Copyright Opticon. All rights reserved. This information is subject to change without prior notice

- Taiwan: Taipei

- Australia: Kariong

B_OPN2001_001

- The Netherlands: Hoofddorp
- France: ISSY Les Moulineaux CEDEX P.R.China: Shanghai
- Germany: Dietzenbach
- Italy: Castel Maggiore (BO) Spain: Valencia
- Sweden: Järfälla
- United Kingdom: Luton, Bedfordshire U.S.A.: Orangeburg, NY Bellevue, WA
- Japan: Warabi City

www.opticon.com



Phone: 1-800-351-9962 Fax: 1-312-212-1800 www.barcodesinc.com

About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of •] ^& \hat{a} \hat{a}

We Owe Our Success To You

Why Choose BarcodesInc?

Dedicated Account A UbU[Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft*



symbol*

AND MORE