

Zebra EM 220™



Pocket-sized printer for mobile receipt printing

Zebra's ultra-compact EM 220 is a convenient mobile receipt printer that fits neatly into a pocket. With intuitive operation and optional Bluetooth® 2.0 wireless connectivity, the EM 220 is easy to use and ideal for customer-facing environments where space is at a premium.

The EM 220 receipt printer provides a flexible solution for an array of applications. The latest addition to the Zebra mobile printer family, the EM 220 printer gives high quality printing at a compelling price.



Key features:

- Pocket-sized and lightweight
- Simple operation
- Single-push-button media-cover release for easy loading and unloading
- Integrated magnetic card reading (Bluetooth printers only)

Ideal for:

- Onboard transportation ticketing
- Law enforcement – issuing fines and fixed penalties
- Retail queue busting
- Hospitality service applications

Get most out of your Zebra put genuine Zebra supplies in!

Zebra offers a wide range of supplies for its printers, all made to a high standard and suitable for a variety of applications.

- Manufactured exclusively for Zebra printers
- Laboratory-tested for optimum performance
- Proven to minimise wear and tear on printhead

▶ For more information, visit www.zebra.com



Specifications at a glance*

Standard Features

- Direct thermal printing 8 dots/mm (203 dpi) print resolution
- 2 MB Flash / 8 MB SRAM memory
- 7.4V, 1.2 Ah Li-Ion battery
- Serial/USB connection
- Tear strip for easy receipt dispensing
- Supports vertical or horizontal printing
- Open access design for easy loading
- Li-Ion charger and belt strap included with printer
- Tolerance of multiple drops up to 1.2m to concrete
- Sensors detects door, open, out of paper, pre-printed media alignment
- LEDs indicate connectivity and battery status

Printing Specifications

Resolution:

- 8 dots/mm (203 dpi) resolution

Memory:

- 2 MB Flash / 8 MB SRAM memory

Maximum print width:

- 50.8 mm (2.0")

Print Speed:

- Print speed: up to 80 mm 3.15"/ per second

Media Specifications

NOTE: For optimum print quality and printer performance, use of genuine Zebra Supplies is recommended.

Media Width:

- 2.28" (+/- 0.2") / 58.0 mm (+/-5mm)

Maximum print width

- 2.0" / 50.8 mm

Maximum roll length

- 40' with 3.2 mil paper

Roll Diameter

- Core OD 18.5±0.5mm (0.728 +/-0.0196")
- Label Roll OD Max. 1.57" / 39.9 mm

Maximum media thickness

- 4 mil / 0.1016 mm

Operating characteristics

Environmental

- Operating Temp. 14° F/-10° C to 122° F/50° C
- Relative humidity: 20% - 70% non-condensing

Electrical Specifications

- Standard battery
 - 7.4 V, 1.2 Ah Li-Ion battery, rechargeable Li-Ion battery

Agency approvals

EMC & Safety Standards

- Europe: CE Mark: CE 0984, DEMKO GS: EN60950-1: 2001
- North America: FCC rules part 15C
- NRTL Safety Approval IEC60950-1:2001

Safety Standards: CB-scheme: IEC60950-1: 2001

- CE Mark, EMC Directive 2004/108/EC, R&TTE Directive 95/5/EC, Radio Spectrum EN300328 v1.6.1
- Low Voltage Directive 2006/95/EC Safety: EN60950-1:2001
- International Marks: UL, FCC, CE, GS, CCC, SRRC, NCC, CB, GOST-R, TELEC, SIG, PSI, C-Tick, OFTA, VCCI, IC, SIRIM, NOM, COFETEL, S-MARK, CNC, ANATEL, WPC, IDA, NTC license

Physical characteristics

Width

- 79.5mm (3.1")

Height

- 126.7mm (5.0")

Depth

- 43.6mm (1.7")

Weight

- 0.24kg (0.52lbs)

*Weight with battery and no media is provided.

Options and accessories

- Optional Bluetooth® v. 2.0 short range connectivity and card reader
- Single battery cradle to be used with charger
- Quad battery charger
- Replacement charger
- Leather case
- Spare battery

Software

- Drivers
 - Win95/98/ME/2000/NT/XP/2003/Vista
 - OPOS drivers
 - SDK/WinCE 4.2, WinCE 5.0 WinCE 6.0

Printer Control Language

- Communicates in printable ASCII characters
- Compatible with mainframe, mini and PC hosts
- Downloadable objects include graphics

Bar Code Symbolologies

- Bar Code Symbolologies: Codabar, ITF, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN 8, EAN 13, EAN 18
- Two-dimensional Bar Codes: PDF 417, MaxiCode, QR Code, Data Matrix

Fonts and graphics

- Character size: Font A: 12 x 24, Font B 9 x 24
- Characters per line: Font A: 32, Font B: 42,
- Character sets: Alphanumeric character: 95
- Extended character: 128 x 30 pages
- International character set support
 - (KOR, CHN, JPN) - 128 x 20 pages, International: 32.

Communication and interface capabilities

- Communication interface: Serial/USB
- Wireless: Bluetooth v. 2.0.

The Zebra mobile printer family

The EM 220 is just a small part of Zebra's mobile printing portfolio. If you need more features such as water-resistance, advanced connectivity or even RFID mobile solutions visit www.zebra.com



For more information, visit www.zebra.com or e-mail mseurope@zebra.com

*Specifications subject to change without notice.

©2010 ZIH Corp. OpenACCESS and all product names and numbers are Zebra trademarks, and Zebra and representation of Zebra Head are registered trademarks of ZIH Corp. All rights reserved. Bluetooth is a registered trademark of Bluetooth SIG, Inc. Windows, Windows NT and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom
Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 E-mail: mseurope@zebra.com Web: www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East & Africa: Dubai, South Africa