

# Steady-selling



Retail



Hospitality



Ticketing



Kiosk

3 inch POS Printer

## SRP-350II

BIXOLON SRP-350II is a 3 inch thermal POS printer to provide all you need. It supports a printing speed of 200mm/sec. Smart Windows driver and other various drivers make the SRP-350II even more attractive and special. The SRP-350II offers simplicity for operator with Easy-paper-loading and ease of USB 2.0 connectivity with interchangeable interfaces and industry standard drivers.



### HIGHLIGHTS



#### Reliable Printing Performance

- A family of the steady-selling SRP-350 line
- Printing speed up to 200 mm/sec



**BIXOLON**<sup>®</sup>

a Better Solution for your Business™

3 inch POS Printer

# SRP-350II



## SPECIFICATIONS

### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

200 mm/sec

**Print Resolution**

180 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.062 ~ 0.075 mm

**Supply Method**

Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxD)**

145 x 203 x 146 mm  
(5.70 x 7.99 x 5.74 inch)

**Weight**

1.65 kg (3.63 lbs.)

**Power**

EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports

### Performance Characteristics

**Memory**

64 Mbit SDRAM, 16 Mbit FlashROM

**NV Image Memory**

256 Kbytes (mono)

128 Kbytes (color)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

Serial, Parallel, Ethernet, USB 2.0 HS

### Environment Characteristics

**Temperature**

Operating: 0~45°C (32~113°F)

Storage: -20~60°C (-4~140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### Reliability

**Printer Unit (MCBF)**

70 Million Lines

**TPH**

150 km

**Auto Cutter**

1.8 Million Cuts

### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver, Mac Driver,  
Virtual COM USB/Ethernet Driver, Utility Program

**SDK**

iOS SDK, Android SDK

### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12x24 Font B: 9x17 Font C: 9x24

KOR, CHN, JPN: 24x24

**Characters Per Line**

Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

**Character Sets**

Alphanumeric: 95

Extended Graphics: 128x37 page

International: 32

**Graphics**

Supporting user-defined fonts, graphics, formats,  
and logos

**Barcode Symbologies**

1D: Coda Bar, Code39, Code93, Code128, EAN-8,  
EAN-13, ITF, UPC-A, UPC-E

2D: PDF417, QR Code

BR-SRP-350II-EN-OCT13

Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

**BIXOLON®**

www.bixolon.com

**BIXOLON Co., Ltd.**

7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

**BIXOLON America Inc.**

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

**BIXOLON Europe GmbH**

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de